

3 Tonnes | Porta Gantry Series | Adjustable

Specifications

Capacity (kg)	Model Number	D Height to Lifting Eye (mm)		E Height Increment (mm)	F Height to Top of Beam (mm)		G Width (mm)	H Height to Top of Roller (mm)		A-Frame Weight (kg)	Castor (Ø)
		Min.	Max.		Min.	Max.		Min.	Max.		
3,000	PGAS03000I (Intermediate)	2178	3178	5 x 200	2499	3499	1726	2581	3581	73	200
3,000	PGAS03000T (Tall)	2869	4069	6 x 200	3199	4399	2021	3281	4481	85	200
3,000	PGAS03000TC3 (X Tall)	3817	5017	6 x 200	4147	5347	2557	4230	5430	91	200
3,000	PGAS03000TC2 (XX Tall)	3917	5517	8 x 200	4248	5848	2733	4330	5930	97	200

Green shading reflects rental inventory.



Beam Data

Capacity (kg)	Model Number	Weight of Beam (kg)	A Beam Length (mm)	B Beam Adjustment (mm)	C Clear Operating Span (mm)	
					Min.	Max.
3,000	PGBS03000-3000B	28	3000	2 x 200	1680	2080
3,000	PGBS03000-3920D	61	3920	4 x 200	2200	3000
3,000	PGBS03000-4570D	70	4570	8 x 200	2050	3650
3,000	PGBS03000-6000D	85	6000	8 x 200	3480	5080

Green shading reflects rental inventory.

- A Beam length
- B Beam adjustment
- C Clear operating span
- D Height to lifting eye
- E Height increment
- F Height to top of beam
- G Width
- H Height to top of roller

