

5 Tonnes | Porta Gantry Series | Adjustable

Specifications

Capacity (kg)	Model Number	D Height to Lifting Eye (mm)		E Height Increment (mm)	F Height to Top of Beam (mm)		G Width (mm)	H Height to Top of Roller (mm)		A-Frame Weight (kg)	Castor (Ø)
		Min.	Max.		Min.	Max.		Min.	Max.		
5,000	PGAS05000IR (Intermediate)	2181	3181	5 x 200	2592	3592	1736	2717	3717	99*	200
5,000	PGAS05000TR (Tall)	2849	4049	6 x 200	3287	4487	2021	3412	4612	109*	200
5,000	PGAS05000TC3R (X Tall)	3800	5000	6 x 200	4238	5438	2557	4362	5562	101	200

Green shading reflects rental inventory.

*Weight includes stabiliser legs.



Beam Data

Capacity (kg)	Model Number	Weight of Beam (kg)	A Beam Length (mm)	B Beam Adjustment (mm)	C Clear Operating Span (mm)	
					Min.	Max.
5,000	PGBS05000-3000D	47	3000	2 x 200	1680	2080
5,000	PGBS05000-4570D	71	4570	8 x 200	2050	3650
5,000	PGBS05000-5500D	85	5500	8 x 200	2980	4580

Green shading reflects rental inventory.

- A Beam length
- B Beam adjustment
- C Clear operating span
- D Height to lifting eye
- E Height increment
- F Height to top of beam
- G Width
- H Height to top of roller

