

Shackles | 125 - 200 Tonnes | Wide Body - Alloy Bolt Type

Material: bow and pin high tensile steel, Grade 8, quenched and tempered

Safety Factor: MBL equals 5 x WLL

Finish: hot dipped galvanized

Temperature Range: -40°C up to +200° C

Certificates: at no extra charges this product can be supplied with a works certificate, certificate of basic raw material, manufacturer test certificate, EC Declaration of Conformity and all shackles starting from 150 tons are supplied with a Lloyd's Register of Shipping Certificate on proof load

Note: +5% forging tolerance on inside width and length



P-6033

Specifications (mm)														
Working load limit	Diameter bow	Diameter pin	Diameter eye	Width eye	Width inside	Length inside	Width bow	Length	Length bolt	Width	Thickness nut	Bearing surface	Weight pin	Weight each
tonnes	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	k mm	l mm	kg	kg
125	85	80	156	85	137	366	220	583	413	390	40	150	18.6	92
200	110	105	201	100	158	481	280	759	480	500	50	205	36.9	205
300	136	134	246	134	195	601	350	946	590	620	70	265	79.4	360

Green shading reflects rental inventory.

